## CUSTOMER PRODUCT SPECIFICATION SHEET

USAGE PRECAUTIONS: CABLES USING 'MICRO' COAX ARE DELICATE:

RoHS Compliant

-WASHER

0.5

## CAB528RF: I-PEX MHF + SMA STRAIGHT BULKHEAD JACK WITH O-RING RATED TO IP67/68 + Ø1.37MM LOW LOSS CABLE, 8GHz

(i) HANDLE WITH CARE.

NOT FORCEFULLY DEFORM WIRES.

ON HANDLING INSTRUCTIONS.

### SPECIFICATIONS:

- 1. I-PEX MHF I PLUG. P/N: 20351-112R-37.
- 2. \phi1.37MM LOW LOSS COAXIAL CABLE, COLOR: BLACK.
- 3. SMA STRAIGHT BULKHEAD JACK WITH O-RING RATED TO IP67/68, P/N: RFCT-SMA108-F37.

#### ENVIRONMENTAL:

- A. BULKHEAD MOUNTED CONNECTOR (RFCT-SMA108-F37) RATED TO THE FOLLOWING SPECIFICATION:
  - i. IP6X DUST TIGHT NO PARTICLE INGRESS.
- ii. IPX7 WATERPROOF FOR 30 MINUTES UP TO 1 METER UNDFRWATER
- iii. IPX8 WATERPROOF FOR 48 HOURS AT 1 METER UNDERWATER.

#### NOTES:

- 1. WORKING FREQUENCY RANGE: DC-8GHz.
- 2. OPERATING TEMPERATURE: -40°C TO +85°C.
- 3. IMPEDANCE: 50 Ohm.

# 0-RING 11.4 0±0.1 $\phi 6.5 \pm 0.1$ 1/4-36UNS-2A RECOMMENDED SMA MOUNTING HOLE 11 4

(ii) DO NOT TWIST: APPLY EXCESSIVE FORCES OR SHARP BENDS TO THE CABLE. DO

(iii) CONSULT CONNECTOR MANUFACTURER'S DATASHEETS FOR DETAILED NOTES

HOW TO ORDER CAB528RF - X X X X - X X - X - 1

"L" LENGTH IN MM


eq: 100MM = 0100(MIN. 0050-MAX.0400

STANDARD = 0100, 0150, 0200)

201-400mm: ±7mm.

Tolerance: 50-200mm: ±5mm.

WASHER AND NUT OPTIONS: BLANK = SEPERATELY PACKED (STANDARD) A = ASSEMBLED WITH CONNECTOR



ORIENTATION OPTIONS:

BLANK = DOES NOT HAVE A FIXED ORIENTATION


F1 = MHF CONNECTION DOWN (L=50-200MM)

F2 = MHF CONNECTION UP (L=50-200MM)

F3 = MHF CONNECTION AND D FLAT SAME ORIENTATION (L=50-200MM)

F4 = MHF CONNECTION AND D FLAT OPPOSITE ORIENTATION (L=50-200MM)

(SEE NOTES 1, 2, 3 AND DIAGRAMS FOR MORE INFORMATION)



Scale:	NTS	THIRD ANGLE		Unstated .X .XX	Tolerances: N/A N/A	
Drawn:	СС	<b>₽</b>	-	.XXX ANGLES	N/A N/A	
App'd:	xxx	Title CABLE ASSEMBLY				
Date: 3 FEB. '24		Revision: 1.2		Unit: mm		H





14.8

Drawing Number: CAB528RF

Sheet 1 of 1 Drawing (C) E and 0 E

(C) THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT

FLAT 5.9

SMA JACK DETAIL DRAWING