CABLE 268 RF: RF CABLE ASSEMBLY, HIROSE U.FL + N S/T BULKHEAD JACK WITH O-RING + 1.37MM CABLE

SPECIFICATIONS :

- 1. HIROSE U.FL PLUG, P/N: U.FL-LP-088
- 2. ϕ 1.37MM COAXIAL CABLE, COLOR: BLACK
- 3. N STRAIGHT BULKHEAD JACK WITH 0-RING (RECT-N003-F78)

NOTES:

- 1. THE ORIENTATION OF CONNECTORS ON DRAWING IS FOR REFERENCE ONLY, IF THE ORDER IS LEFT BLANK THE CONNECTOR WILL NOT HAVE FIXED ORIENTATION.
- 2. FIXED ORIENTATION IS SUGGESTED FOR CABLE LENGTH 50MM TO 200MM. PLEASE SPECIFY THE FIXED ORIENTATIONS FROM THE ORDER CODE (F1, F2, F3,ETC)
- 3. CONTACT GRAD CONN IF THE ORIENTATION YOU REQUIRE IS NOT SHOWN.
- 4. WORKING FREQUENCY RANGE: DC-3GHz.

'F1' ORIENTATION

USAGE PRECAUTIONS: CABLES USING 'MICRO' COAX ARE DELICATE:

- (i) HANDLE WITH CARE.
- (ii) DO NOT TWIST; APPLY EXCESSIVE FORCES OR SHARP BENDS TO THE CABLE. DO NOT FORCEFULLY DEFORM WIRES.
- (iii) CONSULT CONNECTOR MANUFACTURER'S DATASHEETS FOR DETAILED NOTES ON HANDLING INSTRUCTIONS





RECOMMENDED MOUNTING HOLE

HOW TO ORDER

CABLE 268 RF - X X X X - X - XX - 1

"L" LENGTH IN MM: CABLE SIZE OPTIONS:

eg: 100MM = 0100

(MIN. = 0050, MAX. = 2000)

STANDARD = 0100, 0150, 0200)

Tolerance: <50mm: ±2mm. 51–200mm: ±5mm.


201-500mm: ±7mm. >501mm: ±10mm.

 $1 = \phi 1.37$ MM CABLE, COLOR: BLACK BLANK = DOES NOT HAVE A FIXED ORIENTATION

BLANK = DOES NOT HAVE A FIXED ORIENTATION F1 = U.FL CONNECTION DOWN (L=50-200MM)

F3 = U.FL CONNECTION FRONT (L=50-200MM)

(SEE NOTES 1, 2, 3 AND DIAGRAMS FOR MORE INFORMATION)



N BULKHEAD DETAIL DRAWING

WASHER AND NUT OPTIONS:

BLANK = SEPERATELY PACKED (STANDARD)

A = ASSEMBLED WITH CONNECTOR

					l
				<u>′F3′</u>	ORIENTATION
	L				
DATE & DRN	103/17 - NYW RELEASE	706/17 'F3' orientation.	/02/′19 – NYW ove 'F2' orientation.		

ŀ	Scale: NTS	THIRD ANGLE	Unstated .X .XX .XXX .XXX ANGLES	Tolerances: N/A N/A N/A N/A	Material
	Drawn: NYW	$\Rightarrow \Rightarrow$			SEE NOTE
	App'd: XXX	Title CABLE ASSEMBLY			NOT TO SCALE
	Date: 22 FEB. '19	Revision: 1.2	Unit: mm		



Type: Cable 268 RF
CABLE 268 RF

	Drawing Number:			
adconn.com	Sheet 1	of 1		
TIAL AND MUST NOT BE	Drawing (C)	E and O E		