



**GRAD CONN LTD.**

格瑞康實業有限公司

1F 205 Shinde Street, Pingjen City, Taoyuan Hsien, Taiwan 324  
TEL: +886-3-4944743 FAX: +886-3-4923493 <http://www.gradconn.com>

---

## **1.0 SCOPE**

This specifies Pitch 5.08 male header series connector, The connector shall meet the performances, specified here under the condition with the plug connector and the receptacle connector mated. This specification covers the product standards, requirements, and qualification provisions for hard disk and personal computer or other field.

## **2.0 APPLICABLE DOCUMENTS**

At the time of this specifications release, the latest revisions of the following documents were used. These documents shall form a part of this specification as described within this document.

### **Industry Specifications / Standards**

**UL-94** Flammability

**ASTM B-103** Phosphor Bronze or Brass Plate, Rod, Sheet, Strip and Rolled Bar

### **EIA Specifications**

**EIA-364-D** Electrical Connector/Socket Test Procedures Including Environmental Classifications

## **3.0 REQUIREMENTS**

### **3.1 DIMENSIONAL**

Connectors shall meet the physical dimensions specified on the applicable product drawing.

### **3.2 MATERIAL**

Each component shall be constructed of the materials specified within this document.

Substitute materials must meet the performance requirements of this specification.

**3.2.1 Contacts:** Brass or other equivalent copper alloys

**3.2.2 Housings:** Nylon 6T , LCP or Nylon 46, flame retardant 94V-0 per UL-94; or other high performance resin.

### **3.3 FINISH**

**3.3.1 Contact Finish:** See plating drawing.

### **3.4 DESIGN**



GRAD CONN LTD.

格瑞康實業有限公司

1F 205 Shinde Street, Pingjen City, Taoyuan Hsien, Taiwan 324  
TEL: +886-3-4944743 FAX: +886-3-4923493 <http://www.gradconn.com>

---

**3.4.1 Mating:** The connector shall be capable of mating and unmating manually with the test board.

## **3.5 MECHANICAL REQUIREMENTS**

### **3.5.1 Workmanship:**

The product shall be uniform in quality and free from defects, that will adversely affect the product performance.

### **3.5.2 Contact Retention Force:**

The end of a post shall be pushed in a perpendicular to base housing at a constant speed of 25.4 mm / minute. minimum Retention Force for 5N / pin .

### **3.5.3 Durability:**

When measured in accordance with EIA-364-09C, the following details shall apply: 100 mating cycles at a rate of 25.4 mm/minute ,contact resistance 30 mΩ Max.

## **3.6 ELECTRICAL REQUIREMENTS**

### **3.6.1 Current Rating:** 7.9A

When measured in accordance with EIA-364-70, 7.9 A maximum, based on a 30 degree rise over ambient

### **3.6.2 Voltage Rating:** 500V AC/DC.

When measured in accordance with EIA-364-20B,

### **3.6.3 Low Level Circuit Resistance:**

When measured in accordance with EIA-364-23B, Initial:  $\leq 20$  mΩ, after environmental test:  
 $\leq 30$ mΩ. the following details shall apply:

- (a). Current: 20 mA maximum,
- (b). Maximum Open Circuit Voltage: 20 mV DC.

### **3.6.4 Dielectric Withstanding Voltage:**

There shall be of no evidence of flashover when the mated plug and receptacle are tested in accordance with EIA-364-20B, The following details shall apply:

- (a). Voltage: 600V AC at 50 Hz,
- (b). Duration: 60 sec,
- (c). Measurement Points: Measure across a minimum of 10 adjacent and 10 opposing contacts.



GRAD CONN LTD.

格瑞康實業有限公司

1F 205 Shinde Street, Pingjen City, Taoyuan Hsien, Taiwan 324  
TEL: +886-3-4944743 FAX: +886-3-4923493 <http://www.gradconn.com>

---

### **3.6.5 Insulation Resistance:**

Shall be a minimum of 1000 megaohms before conditioning and a minimum of 500 mega ohms after conditioning. When measured in accordance with EIA-364-21C, the following details shall apply:

- (a). Voltage: 1500 V DC/ 1 min.
- (b). Measurement Points: Measure between 10 adjacent and 10 opposing contacts per plug and receptacle.

### **3.6.6 Capacitance:**

Measure the capacitance between adjacent unmated contacts. The capacitance shall not exceed a maximum of 2 pF at 1 KHz.

## **3.7 ENVIRONMENTAL REQUIREMENTS**

**3.7.1 Operating Temperature Range:** -40°C~105°C.

### **3.7.2 Temperature Life:**

After exposure of the unmated connector to a high temperature-operating environment, the contact resistance shall not exceed the value specified in Table 1 (see paragraph 3.6.3). Test shall be in accordance with EIA-364-17B. The following details shall apply:

- (a). Test Condition: 105°C, 96hours.

### **3.7.3 Thermal shock test:**

There shall be no evidence of physical damage when the mated module and socket are subjected to transient acceleration. During and after each shock, the test shall show no evidence of discontinuity greater than 1 microsecond. The test shall be in accordance with EIA-364-32C, Test Condition a,b

- (a). Temperature: -40°C~105°C 5cycles
- (b). Initial, After Test THERMAL:  
Maximum Circuit Resistance: 30 mΩ or bleow.

### **3.7.4 Humidity Test:**

After exposure of the plug and receptacle to a high humidity environment, the insulation resistance shall not be less than 500 megaohms. The dielectric withstanding voltage shall be greater than 600V AC for 1 minute. The low level contact resistance shall not exceed the specified. The test shall be in accordance with EIA-364-31B.



GRAD CONN LTD.

格瑞康實業有限公司

1F 205 Shinde Street, Pingjen City, Taoyuan Hsien, Taiwan 324  
TEL: +886-3-4944743 FAX: +886-3-4923493 <http://www.gradconn.com>

---

a. Test Condition:  $40\pm 2^{\circ}\text{C}$ , 90-95% RH, 96 hrs.

### **3.7.5 Salt Spray:**

After exposure, the contact resistance shall not exceed that specified (see paragraph 3.6.3). The insulation resistance shall not be less than 500 megaohms (see paragraph 3.6.5). The dielectric withstanding voltage shall be greater than 600V AC for 1 minute (see paragraph 3.6.4). The test shall be in accordance with EIA-364-26B, The following details shall apply:

- (a). Test Condition:  $35\pm 2^{\circ}\text{C}$ , 16 hrs, 5% NaCL;
- (b). Special Handling: The mated sockets shall be mildly rinsed in water to remove salt residue and allowed to dry for 24 hours at room temperature before measurements are to be taken.

### **3.7.6 Resistance to Soldering Heat:**

There shall be no evidence of physical damage to the insulator or finished product when the unmated socket is subjected to the reflow soldering process.

The following details shall apply:

- (a). Test Condition: Test connector shall be placed on the p.c. board,
- (b). Pre-Heat Temperature:  $100\sim 150^{\circ}\text{C}$  for 60 seconds maximum,
- (c). Temperature: minimum  $210^{\circ}\text{C}$  for 30 seconds maximum,
- (d). Peak Temperature:  $260\pm 5^{\circ}\text{C}$ ,  $10\pm 5\text{sec}$ .

### **3.7.7 Solderability Test:**

After exposure, the contact solder tails shall have a minimum of 95% solder coverage. The covered area must not show any evidence of voids or pinholes. The test shall be in accordance with EIA-364-71B, the contact solder tails must have solder coverage of 95% up. The plastics have no damaged. The following details shall apply:

- (a). Solder Dwell Time: Contacts shall be held above the solder for 3 to 5 seconds before being immersed in the solder,
- (b). Test Temperature :  $245\pm 3^{\circ}\text{C}$ .

## **4.0 QUALITY ASSURANCE PROVISIONS**

### **4.1 INSPECTION CONDITIONS**



GRAD CONN LTD.

格瑞康實業有限公司

1F 205 Shinde Street, Pingjen City, Taoyuan Hsien, Taiwan 324  
TEL: +886-3-4944743 FAX: +886-3-4923493 <http://www.gradconn.com>

Unless otherwise specified, all inspections shall be performed under the following ambient conditions.

- (a) Temperature: 25±5°C
- (b) Relative Humidity: 30% to 70%
- (c) Barometric Pressure: Local Ambient

## **4.2 QUALIFICATION INSPECTION**

Qualification inspections shall be performed on sample units produced with production equipment.

### **4.2.1 Sample Selection:**

Connectors shall be prepared according to applicable instruction sheets. Samples shall be selected at random from current production. A total of 26 samples are required for the specified test sequence.

### **4.2.2 Test Sequence:**

The sample connectors shall be subjected to the inspections specified in the order shown.

<b>Test Item</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G</b>	<b>H</b>
<b>Sample Size</b>	<b>3</b>	<b>3</b>	<b>3</b>	<b>3</b>	<b>5</b>	<b>3</b>	<b>3</b>	<b>3</b>
Examination of Product	1,5	1,5	1,9	1,7	1,5	1,3	1,3	1,3
Terminal Resistance	2,4	2,4	2,8		2,4			
Insulation Resistance			3,7	2,5				
Dielectric Withstanding Voltage			4,6	3,6				
Temperature Life		3						
Humidity Test				4				
Thermal shock	3							
Solderability								2
Resistance to Soldering Heat							2	
Contact Retention Force						2		
Durability					3			
Salt Spray			5					